

# SymphoniePLUS™

15-channel data logger



"Your systems have many attractive attributes—including quality instrumentation with excellent warranty and support."

— Eddie Sheehan  
Micro Wind Systems  
Ireland

## The Industry Standard

**Expand your wind energy measurement study using NRG Systems SymphoniePLUS™ data loggers.**

Built on the industry-trusted Symphonie data logger platform, PLUS three more anemometer channels.

- **Proven**  
Pre-configured for the wind industry
- **More Anemometers**  
Up to nine anemometer channels — 15 channels total
- **Easy to use**  
Intuitive programming and data software operation
- **Internet Ready**
  - Iridium Satellite
  - Cellular: CDMA, DoCoMo, Worldwide GSM

**Precise. Reliable. Proven.**

Complete Systems | Sensors | Remote Sensors | Tilt-Up Towers | Data Loggers | Turbine Control

Global leader in wind measurement technology





# SymphoniePLUS™ 15-channel data logger

## Specifications

### Description

<b>Instrument type</b>	15 channel internet-enabled wind energy data logger
<b>Applications</b>	<ul style="list-style-type: none"> <li>wind resource assessment</li> </ul>
<b>Sensor compatibility - counter channels</b>	<ul style="list-style-type: none"> <li>NRG #40C anemometer</li> <li>opto anemometer</li> <li>reed switch anemometer</li> <li>rain gauge</li> </ul>
<b>Sensor compatibility - analog channels</b>	<ul style="list-style-type: none"> <li>NRG 200P direction vane</li> <li>NRG 110S temperature</li> <li>Li-Cor 200SA pyranometer</li> <li>NRG BP-20 absolute pressure (requires optional iPack power)</li> <li>RH-5 relative humidity (requires optional iPack power)</li> </ul>
<b>Counter channels</b>	<p>Channels 1-6 and 13-15 are counter inputs:</p> <ul style="list-style-type: none"> <li>channels 1-3 and 13-15 are pre-programmed for NRG #40C anemometers or compatible sensors</li> <li>channels 4-6 use counter Signal Conditioning Modules (SCMs) to configure the channels for other sensors</li> </ul>
<b>Analog channels</b>	<p>Channels 7-12 are analog inputs:</p> <ul style="list-style-type: none"> <li>channels 7 and 8 are dedicated for NRG 200P direction vane</li> <li>channels 9-12 use analog Signal Conditioning Modules (SCMs) to configure the channels for other sensors</li> </ul>

### Data Collection

<b>Sampling interval</b>	2 seconds
<b>Averaging interval</b>	10 minute, fixed
<b>Real time clock</b>	internal battery-backed
<b>Storage medium</b>	32 MB MultiMedia Card (MMC), non-volatile FLASH
<b>Maximum data storage</b>	664 days
<b>Parameters recorded for each channel</b>	<ul style="list-style-type: none"> <li>each 10 minute interval is time/date-stamped</li> <li>average</li> <li>standard deviation</li> <li>min*</li> <li>max*</li> </ul> <p>*min and max not used for wind direction vanes</p>
<b>File format</b>	<ul style="list-style-type: none"> <li>Windows compatible</li> <li>(1) 14 KB binary file per day</li> <li>header includes site, serial number and sensor information</li> </ul>
<b>Software</b>	<p>Symphonie Data Retriever for Windows (included)</p> <ul style="list-style-type: none"> <li>scales raw data</li> <li>creates measurement database for each site</li> <li>creates basic reports</li> <li>maintains site and sensor information</li> <li>configures iPacks</li> </ul>
<b>Reader</b>	Windows compatible MMC reader accesses data stored on MMC
<b>Data delivery</b>	<ul style="list-style-type: none"> <li>MMC cards, and/or internet email via optional iPack: GSM, CDMA (Verizon or Telus) and Iridium Satellite</li> </ul>
<b>Resolution</b>	
<b>Analog measurement resolution</b>	0.1% of full scale (1024 counts)
<b>Counter average stored resolution</b>	0.1% of the value stored
<b>Analog average stored resolution</b>	0.1% of the value stored
<b>Min / Max stored resolution</b>	0.4% of the value stored
<b>Standard deviation stored resolution</b>	4% of the value stored

### Configuration

<b>User interface</b>	<ul style="list-style-type: none"> <li>Liquid Crystal Display (LCD) 4 x 20 characters</li> <li>16 key pad (6 navigation keys plus numeric/phone pad) with audible feedback</li> </ul>
<b>Configurable parameters</b>	<ul style="list-style-type: none"> <li>clock</li> <li>time zone</li> <li>site number</li> <li>display scaling (defaults are provided for each channel based on channel type)</li> </ul>
<b>iPack options</b>	<ul style="list-style-type: none"> <li>iPack configured via serial port connection to your PC</li> <li>serial connection direct to iPack or through logger's iPack access port</li> <li>Symphonie Data Retriever for Windows integrates iPack settings</li> </ul>

### Connections

<b>Sensor wiring</b>	<ul style="list-style-type: none"> <li>sensors connect to removeable field wiring panel</li> <li>ground stud connects to earth ground with included ground cable</li> <li>male DB25 interfaces to one optional iPack communications module</li> <li>iPack access port facilitates field programming and accepts headset for voice calls</li> <li>3 SCM slots for counter channels 4, 5, 6</li> <li>4 SCM slots for analog channels 9, 10, 11, 12</li> </ul>
----------------------	---

### Power requirements

<b>Batteries</b>	<ul style="list-style-type: none"> <li>(2) 1.5 Volt D-Cell Batteries (included)</li> <li>nominal voltage: 1.5 Volts</li> <li>minimum voltage: 0.9 Volts</li> <li>battery life approximately one year, depending on configuration</li> </ul>
<b>External power input</b>	<ul style="list-style-type: none"> <li>provided by an optional iPack</li> </ul>
<b>External solar input</b>	<ul style="list-style-type: none"> <li>provided by an optional iPack</li> </ul>
<b>Other</b>	<ul style="list-style-type: none"> <li>optional iPacks provide 12V power (20mA max.)</li> <li>PV/Battery only iPack provides power to sensors and logger for stand alone configurations</li> </ul>

### Installation

<b>Mounting</b>	<ul style="list-style-type: none"> <li>mounts with 4 bolts (included) to keyed slots inside of metal shelter box</li> <li>shelter box mounts to tower with hose clamps</li> </ul>
<b>Tools required</b>	<ul style="list-style-type: none"> <li>screwdriver for input terminals, included</li> <li>8 mm (5/16 inch) wrench or nut driver for logger mounting screws</li> <li>3/8 inch wrench or nut driver for logger ground nuts</li> </ul>

### Environmental

<b>Operating temperature range</b>	-40°C to 65°C (-40°F to 149°F) Note: display readable -30°C to 55°C (-22°F to 130°F)
<b>Operating humidity range</b>	0 to 100% RH non-condensing
<b>Lifespan</b>	10 years +

### Physical

<b>Weight</b>	1.3 kg (2.6 pounds), including batteries
<b>Dimensions</b>	22.2 cm (8.7") h x 18.8 cm (7.4") w x 7.7 cm (3.0") d, including field wiring panel

### Materials

<b>Faceplate</b>	injection molded black ABS
<b>Buttons</b>	white elastomer dome keypad
<b>Wiring panel</b>	fiberglass-epoxy terminal board, sealed gold plated pins, zinc plated screws and terminals
<b>Enclosure</b>	<p>weatherproof polycarbonate, meets the following specifications:</p> <ul style="list-style-type: none"> <li>NEMA type 4, 4X and 13</li> <li>IEC: IP65</li> </ul>

## Ordering Information

■ SymphoniePLUS 15-channel data logger – Item No. 4289

## To Place Your Order

Contact NRG Sales, 802-482-2255 or visit [nrgsystems.com](http://nrgsystems.com)

110 Riggs Road, Hinesburg, Vermont 05461 USA | [info@nrgsystems.com](mailto:info@nrgsystems.com)